

KAUPA MONTHLY (MAY/2018) BROCHURE- PRODUCT INDEX

PAGE1:

GT-9442-M 31PC TAP & DIE SET

GT-9442-I 31PC TAP & DIE SET

GT-9460 2-TIERS HEIGHT-ADJUSTABLE TOOL CART- 575X460X795MM

GT-9445 CARRY FREE OPERATING PLATFORM

PAGE2:

OI-9125 FLUID TRANSFER PUMP FOR AdBLUE-0.55L < HOT PRODUCT >

OI-9126 TOPPING UP ENGINE OIL

OI-9127 TOPPING UP ENGINE OIL < HOT PRODUCT >

OI-9128 12PC COLLANT REFILLING FUNNEL SET WITH EXTENSION PIPES

OI-9129 1L SANDBLASTING GUN < HOT PRODUCT >

PAGE3:

PC-9109-1 HYDRAULIC RAM LARGE VERSION FEET SET

PC-9317 300MML VALVE TOOL WITH RUBBER

PC-9318 535MML TIRE LEVEL WITH PROTECTOR

WR-9323 3/8" DR. 8" QUICK WRENCH RATCHETING TOOL

WR-9324 1/2" DR. 10" QUICK WRENCH RATCHETING TOOL

PAGE4:

TS-9147 VACUUM PUMP BRAKE BLEEDING KIT

TS-9148 FUEL SYSTEM TESTING AND CLEANING SET < HOT PRODUCT >

TS-9149 EXHAUST BACK PRESSURE SET

TS-9149-A BASIC EXHAUST BACK PRESSURE SET



www.kaupa.com.tw

GT-9442-M

31PC TAP & DIE SET

- 28pc. Taps and Dies: (Metric)
M6 x 0.75, M6 x 1.0,
M8 x 1.0, M8 x 1.25,
M10 x 1.25, M10 x 1.5,
M12 x 1.5, M12 x 1.75,
M14 x 1.5, M14 x 2.0,
M16 x 1.5, M16 x 2.0,
M18 x 1.5, M18 x 2.5

- 1pc. Auto Center punch
- 1pc. Tap Handle (M6-M20)
- 1pc. Die Stock (38MM)



GT-9442-1

31PC TAP & DIE SET

- 28pc. Taps and Dies: (Imperial)
1/4NC20, 1/4NF28,
5/16NC18, 5/16NF24,
3/8NC16, 3/8NF24,
7/16NC14, 7/16NF20,
1/2NC13, 1/2NF20,
9/16NC12, 9/16NF18,
5/8NC11, 5/8NF18

- 1pc. Auto Center punch
- 1pc. Tap Handle (1/4"-3/4")
- 1pc. Die Stock (1-1/2")



GT-9460

2-TIERS HEIGHT-ADJUSTABLE TOOL CART- 575X460X795MM

- Let users adjust shelf height at their own requirement.
- Easy to adjust the height by one man.
- Easy to assemble and dismantle.
- Will not rust, dent, or require painting.
- Lightweight and durable.
- Compact size for shipping.

Model	GT-9460
Dimension	Each plate 455x572 mm Height 533~795 mm
Plate Size	455x572 mm
Upright	Aluminum alloy, 8pcs
Material	Aluminum alloy, PP
Net Weight	3.94 kg
Loading Capacity	Top plate 10 kg Bottom plate 20 kg
Caster 2"	Reinforced Nylon, Swivel x2, Brake x2



GT-9445

CARRY FREE OPERATING PLATFORM

10 FEATURES:

- Plug and Play
- Weightless operation
- Covered steel cable
- Easy step for shifting
- 180° Efficient work zone
- Precise aiming for narrow space
- Mobile service
- Extensive Usage: Up to 66 LBS
- Applications: For Time & Labor-saving work
- Easy repair design

Model	GT-9445
Square Drive	1"
Max Torque	2,800 FT-LBS (3,800NM)
Free Speed	3,500 RPM
Average Air Consumption	18 CFM (0.5m³/min)
Air Inlet	1/2"
Weight	37.6 LBS (17.1 KG)



KAUPA INTERNATIONAL CO.,LTD

E-mail: service@kaupa.com.tw



KAUPA
APP

Android



IOS





www.kaupa.com.tw

OI-9125

FLUID TRANSFER PUMP



- Manual transfer pump with manual operation design.
- Viton seal which is suitable for diesel, AdBlue and low corrosive fluid.
- Transparent composite plastic for viewing fluid.
- Scale on the syringe body.

OI-9126

TOPPING UP ENGINE OIL



- Material: Alum. type (if you need adaptor suitable car model, pls contact us.)

OI-9127

TOPPING UP ENGINE OIL



- Material: Plastic type (if you need adaptor suitable car model, pls contact us.)

OI-9128

12PC COLLANT REFILLING FUNNEL SET WITH EXTENSION PIPES



- For anti-spill coolant refilling and air bleeding
- Includes 4 extension pipes for confined space or tricky angles
- Transparent lower chamber displays the amount of air bubbles remaining in the radiator
- Includes adapters with nylon covers to reduce heat transfer resulted from air bleeding
- Special design of connector to adapters provides anti-spill feature
- Funnel capacity: 1,600ml / 54.1 Oz. Large capacity suitable for works on trucks and heavy duty vehicles

OI-9129

1L SANDBLASTING GUN



KAUPA INTERNATIONAL CO.,LTD

E-mail: service@kaupa.com.tw



Android



IOS





www.kaupa.com.tw

PC-9109-1

HYDRAULIC RAM LARGE VERSION FEET SET

- 12 Ton hydraulic spindle
- For 4 and 5-bolt wheel hubs
- Flange diameter: Ø115-215mm
- Hub diameter: Ø75-100mm
- Spindle control both by hand and with ratchet as possible



PC-9317

300MML VALUE TOOL WITH RUBBER

- Material: S45C FINISH: Chrome plated
- Length: 300mmL
- One side for Steel wheel and another side for Aluminum wheel

- Feature:
- Use this tool to install the valve.
- The aluminum wheel will not get damage with this plastic protection.



PC-9318

535MML TIRE LEVEL WITH PROTECTOR



- Material: Drop forged Cr-V steel W/Protector Nylon 66 +GF 30%
- Design especially for wheel repair and protect your aluminum wheel without damage.
- Size: 21"
- Length: 535mmL

WR-9323

3/8" DR. 8" QUICK WRENCH RATCHETING TOOL



WR-9324

1/2" DR. 10" QUICK WRENCH RATCHETING TOOL



KAUPA INTERNATIONAL CO.,LTD

E-mail: service@kaupa.com.tw



Android



IOS





www.kaupa.com.tw

TS-9147

VACUUM PUMP BRAKE BLEEDING KIT

Contents:

- Vacuum pump× 1
- Vacuum hose(24")× 1
- Tapered hose adapter× 1
- Tee fitting× 1
- Universal adapter× 1



TS-9148

FUEL SYSTEM TESTING AND CLEANING SET



TS-9149

EXHAUST BACK PRESSURE SET

- Enables technician to test exhaust back pressure through oxygen sensor.
- Oxygen sensor adapter includes M12 and M18 thread.
- The special 2-1/4 in gauge has two multi-colored bands-idle 2500RPM, with pressure shown in PSI and bar.
- High pressure braided stainless steel casing hose • long 1.87m.



TS-9149-A

BASIC EXHAUST BACK PRESSURE SET

- Enables technician to test exhaust back pressure through oxygen sensor.
- Oxygen sensor adapter includes M12 and M18 thread.
- Pressure Range: 0~ 20 PSI / 0-1.5 kg/cm2.
- High pressure braided stainless steel casing hose • long 3.03m.



KAUPA INTERNATIONAL CO.,LTD

E-mail: service@kaupa.com.tw



Android



IOS

