

KAUPA MONTHLY (JUNE/2018) BROCHURE- PRODUCT INDEX

PAGE1:

GT-9449 2-IN-1 LED FOCUS ADJUSTABLE FLASHLIGHT COB WORKLIGHT
8W COB LED+120LUMENS 3W TIP LIGHT
GT-9450 2-IN-1 LED FOCUS ADJUSTABLE FLASHLIGHT COB WORKLIGHT
8W COB LED+3W TIP UV LIGHT

PAGE2: < HOT PRODUCT>

OI-9085 EXTRACTION SYRINGE- 1L W/ 5PCS ADAPTORS <VITON-DIESEL FUEL>
OI-9088 EXTRACTION SYRINGE- 1L <NBR>
OI-9088A EXTRACTION SYRINGE- 1L < VITON>
OI-9089 EXTRACTION SYRINGE- 0.2L <EPDM>
OI-9089SA EXTRACTION SYRINGE- 0.2L< VITON>

PAGE3:

PC-9320 11PCS AIR IMPACT INJECTION NOZZLE PULLER SET
PC-9320G 12PCS AIR IMPACT INJECTION NOZZLE PULLER SET
WR-9325 8" QUICK WRENCH CONNECTOR
WR-9326 12" QUICK WRENCH CONNECTOR
WR-9327 10.5" QUICK DUAL WRENCH TOOL

PAGE4:

TT-9253 BELT INSTALLATION TOOL KIT
TT-9254 AUDI CAMSHAFT SPACER AND PIN SET < HOT PRODUCT>
TT-9255 3/8" CAMSHAFT ADAPTOR SOCKET-VAG
ET-9295-1 PLASTIC SUMP PLUG TO SUIT FORD
ET-9295-2 PLASTIC SUMP PLUG TO SUIT FORD & PSA
ET-9295-3 PLASTIC SUMP PLUG TO SUIT BMW



www.kaupa.com.tw

GT-9449

2-IN-1 LED FOCUS ADJUSTABLE FLASHLIGHT COB WORKLIGHT 8W COB LED+120LUMENS 3W TIP LIGHT



GT-9450

2-IN-1 LED FOCUS ADJUSTABLE FLASHLIGHT COB WORKLIGHT 8W COB LED+3W TIP UV LIGHT



Caution :

- A. LED Max power: 320 Lumens 8W COB LED + 120 Lumens 3W Tip Light. (GT-9449)
LED Max power: 320 Lumens 8W COB LED + 3W Tip UV Light. (GT-9450)
- B. Power output: 5.0V 1000 mAh.
- C. Charger time: 3.5~4.0 hours.
- D. Active time: 5.5 hours+ (GT-9449)
Active time: 3 hours+ (GT-9450)

- E. Storage temperature: -20°C to 70°C
- F. Operation temperature: -5°C to 50°C
- G. Charger input: AC100~240V 50/60 Hz.
- H. Keep the LED light away from fire / water or heat / damp place.
- I. Do not immerse the LED light in water / solvent.
- J. Do not shine the LED light directly on anybody's eyes.



KAUPA INTERNATIONAL CO.,LTD

E-mail: service@kaupa.com.tw



Android



IOS





www.kaupa.com.tw

OI-9085

EXTRACTION SYRINGE- 1L W/ 5PCS ADAPTORS

• VITON(BROWN COLOR) – DIESEL FUEL



OI-9088

EXTRACTION SYRINGE- 1L

• NBR (BLACK COLOR)-
transmission oil, gear oil,
engine oil, differential fluid



OI-9088A

EXTRACTION SYRINGE- 1L



• VITON(BROWN COLOR)-automotive fluid-transmission oil,
gear oil, engine oil, differential fluid, anti freeze, break fluid

OI-9089

EXTRACTION SYRINGE- 0.2L



• EPDM(GRAY COLOR) -
brakd fluid, anti-freeze, coolant

OI-9089SA

EXTRACTION SYRINGE- 0.2L



• VITON(BROWN COLOR)-
automotive fluid-transmission oil, gear oil,
engine oil, differential fluid, anti freeze, break fluid

KAUPA INTERNATIONAL CO.,LTD

E-mail: service@kaupa.com.tw



Android



IOS





www.kaupa.com.tw

PC-9320 / 9320G

9320 11PCS AIR IMPACT INJECTION NOZZLE PULLER SET

9320G 12PCS AIR IMPACT INJECTION NOZZLE PULLER SET WITH AIR IMPACT GUN



PC-9320



PC-9320G

PC-9320 & 9320G

- Material: S45C W/Cr-Mo Steel Black plated
- Clamping size: 10-20mm
- Total length: 510mmL
- Adaptor: M14x1.5 for DELPHI
- Adaptor: M20x1 for DENSO
- Adaptor: M27x1 for SIEMENS
- Adaptor: Puller W/M14x1.5P
- Handle: 110mmL
- Adaptor: M17x1 for Bosch
- Adaptor: M25x1 for SIEMENS
- Adaptor: M27x1.0 for Bosch injector nozzle

• Air Impact Gun x 1pcs (PC-9320G only)

Feature:

Special design for the holding the sliding rod and pulling out the injector with air hammer. Save time to work with this tool.

WR-9325

8" QUICK WRENCH CONNECTOR



WR-9326

12" QUICK WRENCH CONNECTOR



WR-9327

10.5" QUICK DUAL WRENCH TOOL



KAUPA INTERNATIONAL CO.,LTD

E-mail: service@kaupa.com.tw



Android



IOS





www.kaupa.com.tw

TT-9253

BELT INSTALLATION TOOL KIT



TT-9254

AUDI CAMSHAFT SPACER AND PIN SET



- Applications: Audi- A3, A4, A5, A6, Q3, Q5, TT, Seat – Alhambra, Altea, Exeo, Leon, Toledo, Skoda – Octavia II, Superb II, Yeti, Volkswagen – Beetle, CC, EOS, Golf VI, Jetta, Passat, Scirocco, Sharan, Tiguan
- Applications include: 1.8/2.0 TFSi petrol engines 4 valve Petrol TFSi Direct Injection
- Equivalent to OEM T40196 - Used to ensure the camshaft sliding components do not move while dismantling and assembling the engine cylinder head
- Equivalent to OEM T40191 - Used to hold the sliding components of the camshaft in their correct position while removing and fitting the camshaft in the cylinder head.
- Fits engines from as early as 2008 onwards

TT-9255

3/8" CAMSHAFT ADAPTOR SOCKET-VAG



- Application: VAG 1.8/2.0LT 4v TFSi engines (Generation 111) from 2016 onwards
- New tooling required due to a change in the inlet camshaft adjuster profile
- Equivalent to OEM T10567
- Used to turn and hold the inlet camshaft during timing chain service - 3/8"D
- Also available Laser 6785 equivalent to OEM T40266 for use on pre 2016 engines

ET-9295-1

PLASTIC SUMP PLUG TO SUIT FORD



- Replaces Ford 1830727
- Complete with a rubber sealing ring

ET-9295-2

PLASTIC SUMP PLUG TO SUIT FORD & PSA



- Replaces Peugeot Citroen OEM 9801444780.
- Replaces Ford OEM 1871598.
- Complete with a rubber sealing ring

ET-9295-3

PLASTIC SUMP PLUG TO SUIT BMW



- Replaces BMW OEM 11137605018.
- Complete with a rubber sealing ring.

KAUPA INTERNATIONAL CO.,LTD

E-mail: service@kaupa.com.tw



**KAUPA
APP**

Android



IOS

