

KAUPA MONTHLY (DECEMBER/2018) BROCHURE- PRODUCT INDEX

PAGE1:

- ET-0091-1 8" HOSE PINCH OFF PLIERS
- ET-0091-2 10" HOSE PINCH OFF PLIERS
- ET-0091-3 12" HOSE PINCH OFF PLIERS
- ET-9017K OIL DRAIN REPAIR KIT-M11\*1.5P
- ET-9313 MULTI-ANGLE HYDRAULIC CYLINDER STAND < HOT PRODUCT >
- ET-9292 16PCS- 3/8" OIL DRAIN PLUG KEY SET

PAGE2:

- ET-9301 INTAKE MANIFOLD PIPE RELEASE TOOL-VAG 2PCS < HOT PRODUCT >
- ET-9303 SEAL RING INSTALLATION TOOL DV6 (16V)
- ET-9304 RELEASE TOOL
- ET-9305 DIESEL FUEL FILTER COMPRESSOR TOOL-VAG < HOT PRODUCT >
- ET-9308 FUEL TANK LOCK RING TOOL < HOT PRODUCT >
- ET-9309 EGT SENSOR SOCKET SET

PAGE3: < HOT PRODUCT >

- GT-9475 1/2" SQ DR IMPACT DRIVEN WHEEL HUB CLEAN DEVICE-EUROPEAN STYLE  
160MM\*65MM
- GT-9475-1 1/2" SQ DR IMPACT DRIVEN WHEEL HUB CLEAN DEVICE-EUROPEAN STYLE  
200MM\*75MM
- GT-9475-2 1/2" SQ DR IMPACT DRIVEN WHEEL HUB CLEAN DEVICE-STRIP DISC  
160MM\*65MM
- GT-9475-3 1/2" SQ DR IMPACT DRIVEN WHEEL HUB CLEAN DEVICE-STRIP DISC  
200MM\*75MM

PAGE4: < HOT PRODUCT >

- PT-9029 14.4V 3 IN 1 DRIVER
- PT-9030 12V 3 IN 1 DRIVER
- PT-9035 7.2V BATTERY CAULKING DISPENSER 585ML DUAL CARTRIDGES (3:1)
- PT-9036 7.2V BATTERY CAULKING DISPENSER 600ML DUAL CARTRIDGES (1:1)

WR-9334 SERIES 90T QUICKET REVERSIBLE WRENCH

- 9334-5/16** 90T QUICKET REVERSIBLE WRENCH 5/16" x 140L
- 9334-3/8** 90T QUICKET REVERSIBLE WRENCH 3/8" x 160L
- 9334-7/16** 90T QUICKET REVERSIBLE WRENCH 7/16" x 165L
- 9334-1/2** 90T QUICKET REVERSIBLE WRENCH 1/2" x 178L
- 9334-9/16** 90T QUICKET REVERSIBLE WRENCH 9/16" x 190L
- 9334-5/8** 90T QUICKET REVERSIBLE WRENCH 5/8" x 210L
- 9334-11/16** 90T QUICKET REVERSIBLE WRENCH 11/16" x 225L
- 9334-3/4** 90T QUICKET REVERSIBLE WRENCH 3/4" x 247L



www.kaupa.com.tw

**ET-0091-1 / 0091-2 / 0091-3**

- 0091-1** 8" HOSE PINCH OFF PLIERS
- 0091-2** 10" HOSE PINCH OFF PLIERS
- 0091-3** 12" HOSE PINCH OFF PLIERS



**ET-9313**

**MULTI-ANGLE HYDRAULIC CYLINDER STAND**

- This holder is used in connection with a transmission jack to support hydraulic cylinder and the tools driven by it. (Retaining Ø for transmission jack: 30mm)
- This device enables the easy and labor-saving work of all those tools which are driven by the hydraulic cylinder. (Ring I.D. Ø 80.5mm)
- Multiple angle makes the undercar works much faster and easier than before.
- Safety screws keep it in the right position.



**Application**



**ET-9017K**

**OIL DRAIN REPAIR KIT-M11\*1.5P**

**FEATURES:**

- Kit for repairing damaged, stripped, or worn drain plug hole by enlarging the threads with taps provided and new (and bigger) drain plugs with copper washers.
- Suitable for cars with M10 x P1.50 drain plugs:
  - \***Citroen / Peugeot (oil pan)**  
1.4/1.6/1.9/2.2 HDi diesel engines from 2000
  - \***Ford (oil pan)**  
1.4/1.6 TDCi diesel engines from 2005
  - \***Land Rover (oil pan)**  
2.2D (Freelander2) from 2007
  - \***Mazda (oil pan)**  
1.4/1.6 diesels from 2003
  - \***Mini cooper (oil pan)**  
Diesels (PSA engine) from 2007
  - \***Volvo (oil pan)**  
1.6 diesels from 2005
  - \***Jeep (transmission pan)**  
83504041 Cherokee, Comanche & XJ from 1991
  - \***Lexus (transmission pan)**  
90341-10006 GS300, LS400 & SC400 from 1991
  - \***Toyota (transmission pan)**  
Corolla and Matrix



**ET-9292**

**16PCS- 3/8" OIL DRAIN PLUG KEY SET**



- Suitable for sump plugs engines, gear box and back axle.
- Hex key 8/10/12/13/14/17mm
- Square: 8/10mm      • Star (Torx): T45
- Sockets (Magnet): 13/ 14/ 17/ 18/ 19/ 21mm

**KAUPA INTERNATIONAL CO.,LTD**

E-mail: service@kaupa.com.tw



**KAUPA APP**

Android



IOS



## ET-9301

### INTAKE MANIFOLD PIPE RELEASE TOOL-VAG 2PCS



- Intake manifold pipe release tool suitable for Volkswagen, Audi, Seat and Skoda
- For releasing the intake manifold pipe clips fitted to 1.0, 1.2, 1.4 direct injection, turbocharged petrol engines.
- Applications include: Volkswagen Golf 2013<, Audi A3, Q3 2013<, Seat Leon 2013, Ibiza 2008<, Ateca and Skoda Octavia 2013<
- Equivalent to OEM T10527 and T10527/1
- 2 sizes of clip designed to slide in place as indicated by OEM instructions

## ET-9304

### RELEASE TOOL



- Used in conjunction for releasing quick-connecting locks on A/C lines.
- Used on Porsche Macan.

## ET-9303

### SEAL RING INSTALLATION TOOL DV6 (16V)



- Applicable to PSA 1.6 16V (DV6) Diesel engines.
- For example, fitted to Peugeot: 1007, 2008, 206, 206 CC, 207, 207 CC, 208, 3008, 301, 307, 308, 308 CC, 4008, 407, 5008, 508, Expert III, Partner I, Partner II, Partner III; Citroën: Berlingo, Berlingo II, Berlingo III, C2, C3 I, C3 II, C3 III, C3 Picasso, C4, C4 II, C4 Picasso, C4 Picasso II, C4 Grand Picasso, C4 Grand Picasso II, C4 Sedan, C4 Aircross, C5 II, C5 III, C-Elysee, Dispatch, Jumpy III, DS3, DS3 Convertible, DS4, DS5, Xsara Picasso; Fiat: Scudo; Volvo: C30, S40, S80, V50, V70; Ford: C-Max, Fiesta, Focus, Focus C-Max, Fusion; Mazda: 2, 3, 5 and Suzuki: SX4, SX4 Classic. (Engine codes: DV6, G8DA, G8DB, HHDA, HJA, HHJB, D4164T, Y6, 9HX.)

## ET-9308

### FUEL TANK LOCK RING TOOL



- Vauxhall/Opel Applications include: Antara from 2007, Astra-J from 2010, Insignia from 2009, SIGNUM 2003 to 2008, Vectra-C 2003 to 2008. Equivalent to Vauxhall/Opel OEM EN-48279
- Applications: Mercedes Benz W204/W207/W212 E & C Class
- Applications: BMW/F01/F02/F10/F12, 7, 6 & 5 series
- Applications: Volvo T4/T5 engine 2010 onwards and S40, V40

## ET-9305

### DIESEL FUEL FILTER COMPRESSOR TOOL-VAG



- Diesel fuel filter compressor tool for Audi, Volkswagen, Skoda, Seat
- Designed for vehicles with the metal bodied UFI paper diesel fuel filter
- Applications: Audi, Volkswagen, Skoda, Seat
- Allows the re-assembly of the filter housing without bending or damaging the gasket face or gasket material with hands free operation.
- When fitted the filter lid is held down and the filter screws can be fitted. The filter lid is compressed onto the filter body with no need to lever against potentially fragile inner wing panels as per VAG guidelines

## ET-9309

### EGT SENSOR SOCKET SET



- This set of sockets is designed to remove exhaust temperature sensors.
- Due to heat cycles and the corrosive environment in the modern diesel exhaust system the EGT sensors become very difficult to remove without damaging them.
- This set of sockets is designed to drive all 6 sides of the hex equally to reduce the chance of damage.
- The 3 different sizes and two different styles will remove most if not all EGT sensors used on cars, light, medium, and heavy-duty trucks on the road today





www.kaupa.com.tw

### GT-9475 / 9475-1

**9475** 1/2" SQ DR IMPACT DRIVEN WHEEL HUB CLEAN DEVICE-EUROPEAN STYLE  
160MM\*65MM

**9475-1** 1/2" SQ DR IMPACT DRIVEN WHEEL HUB CLEAN DEVICE-EUROPEAN STYLE  
200MM\*75MM



#### INTRODUCTION:

The Impact driven wheel hub clean devices (Wheel hub buddy and wheel hub bearing housing buddy) for Europe type vehicle wheel hub


The European type wheel hub and hub bearing housing cleaning device Impact driven abrasive devices cleans the wheel and hub contact surfaces. Burned in corrosion residues are completely removed in a quick and easy process. Actual process time per hub is about 3-25 seconds depending on the thickness. Process time per hub is about 3-25 seconds.



#### FEATURE:

- The cleaning disc and holder combine a progressive abrasive disc construction with an innovative center hole locking and loosening devices. These are bonded by the abrasive strip material for improved productivity. The system removes rust and corrosion from the hub bearing quickly, even in hard-to-reach places.
- The attachment provides quick disc changes with the convenience of running high-speed tools.
- All this adds up to saving time, increasing speed and effective surface removal and cleaning.
- The replacement disc sizes are for:  
A. the RV truck and bus is about the 300mm up to 500mm for the center hole size from 180 up to 250mm  
B. For cars 160mm in diameter and the center hose size is about 60mm  
C. For the pickup trucks and others diameter in 200mm

- Wheel hub and wheel rim cleaning for Sedan & SUV; Wheel hub and wheel rim cleaning for RV, truck and bus
- The replacement disc size for wheel hub and wheel rim cleaning for Sedan & SUV is about 160mm up to 200mm, There are two different sizes available : The center hole size 65mm x160mm (GT-9475-2) & the 75mm x 200mm (GT-9475-3)



**KAUPA INTERNATIONAL CO.,LTD**

E-mail: [service@kaupa.com.tw](mailto:service@kaupa.com.tw)



Android



IOS



## PT-9029 / 9030

**9029** 14.4V 3 IN 1 DRIVER


**9030** 12V 3 IN 1 DRIVER

Tool	PT-9029	PT-9030
Rated voltage	DC 14.4V	DC 12V
Max torque	110N.m	90N.m
No load speed(RPM)	0~3000	0~3000
I.P.M	4000	4000
B.P.M	30000	30000
Weight (with battery)	1.15kg	1.1kg
Wood screw (mm)	5.1x50	5.1x50
Machine screw (mm)	5.1x50	5.1x50
Concrete	Ø3~Ø6	Ø3~Ø6



## PT-9035

7.2V BATTERY CAULKING DISPENSER 585ML  
DUAL CARTRIDGES (3:1)



Control L & M


Function:	Control (M)	Control (L)
OFP: (Over Force Protection)	1-8	8 Speed Only
Anti-Drip:	○	○
LED Light:	Lighting / Alarm Indicator	Lighting Only
OVP: (Over Voltage Protection)	○	X
OTP: (Over Temperature Protection)	○	X
OCP: (Over Current Protection)	○	X
LVP: (Low Voltage Protection)	○	X
Dosing System:	○	X

• Remark: 2 different type option : L type and M type

MODE	VOLTS	WEIGHT (including battery)	WEIGHT (including case)	MAX.FORCE	NO LOAD SPEED	SIZE(mm)
PT-9035	7.2V Li-ion Battery	1.68kg (3.70 lb)	3.30kg (7.28 lb)	(L) 450kgf±45//990lbf±100// 4410N±441 (M) 600kgf±60//1320lbf±132// 5880N±588	4.0mm/sec	410(L)x225(H)x 97(W) (16.1"x8.9"x3.8")
PT-9036	7.2V Li-ion Battery	1.74kg (3.85 lb)	3.37kg (7.42 lb)	(L) 450kgf±45//990lbf±100// 4410N±441 (M) 600kgf±60//1320lbf±132// 5880N±588	4.0mm/sec	387(L)x225(H)x 112(W) (15.2"x8.9"x4.4")

## PT-9036

7.2V BATTERY CAULKING DISPENSER 600ML  
DUAL CARTRIDGES (1:1)





www.kaupa.com.tw

### WR-9334 SERIES

- 9334-5/16 90T QUICKET REVERSIBLE WRENCH 5/16" x 140L
- 9334-3/8 90T QUICKET REVERSIBLE WRENCH 3/8" x 160L
- 9334-7/16 90T QUICKET REVERSIBLE WRENCH 7/16" x 165L
- 9334-1/2 90T QUICKET REVERSIBLE WRENCH 1/2" x 178L
- 9334-9/16 90T QUICKET REVERSIBLE WRENCH 9/16" x 190L
- 9334-5/8 90T QUICKET REVERSIBLE WRENCH 5/8" x 210L
- 9334-11/16 90T QUICKET REVERSIBLE WRENCH 11/16" x 225L
- 9334-3/4 90T QUICKET REVERSIBLE WRENCH 3/4" x 247L




### USING INSTRUCTION

**STEP 1.** Pushing forward and keep your hand on.



**STEP 2.** Loosing screws:  
Turn counterclockwise (Right)

Lucking screws:  
Turn clockwise (Left)



**STEP 3.** Releasing pushing then start operating.

**KAUPA INTERNATIONAL CO.,LTD**

E-mail: [service@kaupa.com.tw](mailto:service@kaupa.com.tw)



Android



IOS

